

I. Amendments to the Claims

This listing of claims replaces without prejudice all prior versions and listings of claims in the application:

Listing of Claims:

1. (Currently Amended) Apparatus for recognizing an input data stream, comprising:

a receiver for receiving the input data stream;

an interface for randomly selecting any one portion of the received data stream, and forming a first plurality of feature time series waveforms respectively corresponding to ~~spectrally~~ distinct portions of the received data stream;


a memory for storing a second plurality of feature time series waveforms; and

processor structure for correlating the first plurality of feature time series waveforms with the second plurality of feature time series waveforms, and for designating a recognition when a statistic of correlation values between the first plurality of feature time series waveforms and at least one of the second plurality of feature time series waveforms reaches a predetermined value.

2. (Original) Apparatus according to Claim 1, wherein the data stream comprises audio data.

3. (Original) Apparatus according to Claim 1, wherein said data stream comprises video data.

4. (Original) Apparatus according to Claim 1, wherein said memory stores a second plurality of feature time series waveforms, which correspond to an entire broadcast work.

 5. (Currently Amended) Apparatus according to Claim 1, further comprising a scheduler for (i) switching said receiver to a different input data stream after said processor designates the recognition and (ii) scheduling the sampling interval for each of said second plurality of feature time series waveforms.

6. (Currently Amended) Apparatus according to Claim 1, wherein said interface selects a plurality of ~~overlapping~~ portions of the received data stream to form the first plurality of feature time series waveforms.

7. (Currently Amended) Apparatus according to Claim 1, wherein said interface rank-orders the first plurality

of feature time series waveforms according to their information content to access a map of most likely candidate patterns.

8. (Currently Amended) Apparatus according to Claim 1, wherein said processor structure correlates the ~~most descriptive feature of the~~ first plurality of feature time series waveforms with features from each time segment of each of the second plurality of feature time series waveforms stored in memory in an order corresponding to the descriptiveness of each of the second plurality of feature time series waveforms.

*Al
and*
9. (Original) Apparatus according to Claim 1, wherein said receiver normalizes the input data stream to a fixed total power.

10. (Original) Apparatus according to Claim 1, wherein said interface performs a fast Fourier transformation on the received data stream to produce the first plurality of feature time series waveforms.

11. (Currently Amended) Apparatus according to Claim 1, wherein said interface integrates the received data stream over each of a plurality of spectral parameters and then performs a ~~polyphase~~ decimating filter function on the

integration result to produce the first plurality of feature time series waveforms.

12. (Original) Apparatus according to Claim 1, wherein said processor structure designates a recognition which includes a time position of the first plurality of feature time series waveforms within the received input data stream.

13. (Original) Apparatus according to Claim 1, wherein the input data stream comprises a broadcast work, and wherein the processor structure correlates (i) the first plurality of feature time series waveforms which represents any randomly-selected portion of the broadcast work, and (ii) the second plurality of feature time series waveforms which represents the entire broadcast work.

PH
ant

14. (Currently Amended) Apparatus according to Claim 1, wherein said processor correlates the first plurality of feature time series waveforms with the second plurality of feature time series waveforms by computing ~~the~~ a plurality of partial pattern recognitions between the first plurality of feature time series waveforms and templates which correspond to the second plurality of ~~features~~ feature time series waveforms, said processor estimating false alarm probabilities for each of the first plurality of feature time series waveforms, said

processor statistically combining said probabilities to estimate an overall probability that a possible detection is random.

15. (Currently Amended) Apparatus according to Claim 1, wherein said memory stores the second plurality of ~~features~~ feature time series waveforms which are time-overlapped with respect to each other, and wherein said processor zero-fills each of the first plurality of feature time series waveforms to double their lengths prior to correlation.


And
16. (Original) Apparatus according to Claim 1, wherein said processor designates of plurality of potential recognitions after a plurality of correlation probability values reaches the predetermined value, said processor then repeating the correlating and designating functions until only one of the second plurality of feature time series waveforms is designated as corresponding to the input data stream.

17. (Currently Amended) Apparatus for forming video features from an input stream, comprising:

a receiver for receiving an input video stream which corresponds to a video screen having a plurality of

regions, the video screen comprising a plurality of pixels having intensity and color; and

processor structure for (i) receiving the video stream from the receiver, (ii) integrating at least one of the intensity and the color of video signals corresponding to each of the plural areas of the video screen, (iii) forming a set of low rate time series data streams from the integrated video signals, (iv) forming overlapping time intervals of the multiple feature streams such that the overlapping time intervals encompass the entire received video frame sequence, (v) determining the most distinctive information from each time interval, (vi) rank-ordering the features of the time interval segments according to their distinctness, (vii) transforming the rank-ordered time interval segments to produce complex spectra, and (viii) storing the formed data as video features.




18. (Currently Amended) Apparatus according to Claim 17, wherein the processor forms the set of low rate time series data streams by ~~polyphase-decimating-filtering~~ the integrated video signal.

19. (Currently Amended) Apparatus for forming audio features from an input audio stream, comprising:

a receiver for receiving the input audio stream and

separating the received audio stream into a plurality of different frequency bands; and

processor structure for (i) extracting energy from each of the plurality of frequency bands, (ii) integrating the energy extracted from each of the plurality of frequency bands, (iii) forming multiple feature streams from the integrated energy, (iv) forming overlapping time intervals of the multiple feature streams such that the overlapping time intervals encompass the entire received audio stream, (v) determining the most distinctive information from each time interval, (vi) rank-ordering the features of the time interval segments according to their distinctness, and (vii) transforming the rank-ordered time interval segments to produce complex spectra; and

 a memory for storing the transformed complex spectra.

20. (Currently Amended) A method for recognizing an input data stream, comprising the steps of:

receiving the input data stream;


randomly selecting any one portion of the received data stream;

forming a first plurality of feature time series waveforms respectively corresponding to ~~spectrally~~ distinct portions of the received data stream;

rank ordering features of the first plurality of waveforms according to their distinctiveness;

~~storing~~ retrieving a second plurality of feature time series waveforms;

correlating the first plurality of feature time series waveforms with the second plurality of feature time series waveforms in an order corresponding to (i) a map of candidate patterns from the second plurality of feature time series waveforms that best match the rank ordering of the first plurality of feature time series waveforms and (ii) the rank ordering of second plurality of feature time series waveforms; and

 designating a recognition when a correlation probability value between the first plurality of feature time series waveforms and at least one of the second plurality of feature time series waveforms reaches a predetermined value.

21. (Currently Amended) A method for forming video features from an input video stream, comprising the steps of:

receiving an input video stream which corresponds to a video screen having a plurality of regions, the video screen comprising a plurality of pixels having ~~intensity~~ luminance and ~~color~~ chrominance;

~~integrating~~ averaging at least one of the intensity

and the color of video signals corresponding to each of the plural areas of the video screen;

forming a set of low rate time series feature data streams from the integrated video signal;

forming overlapping time intervals of the multiple feature streams such that the overlapping time intervals encompass the entire received video stream;

determining the most distinctive information from each time interval;

rank-ordering the features of the time interval segments according to their distinctness;

transforming the rank-ordered time interval segments to produce complex spectra; and

storing the transformed complex spectra as video features.

22. (Currently Amended) A method for forming audio features from an audio stream, comprising the steps of:

receiving the input audio stream and separating the received audio stream into a plurality of different frequency bands;

extracting energy from the plurality of frequency bands;

integrating the energy extracted from each of the plurality of frequency bands;

forming multiple feature streams from the integrated energy;

forming overlapping time intervals of the multiple feature streams such that the overlapping time intervals encompass the entire received audio stream;

determining the most distinctive information from each time interval;

rank-ordering features of the time interval segments according to their distinctiveness;

transforming the rank-ordered time interval segments to produce complex spectra; and

storing the transformed complex spectra as audio features.

Al
cont

23. (Currently Amended) A computer readable storage medium for storing a program which causes one or more computers to recognize an input data stream, the stored program causing the one or more computers to:

receive the input data stream;

randomly select any one portion of the received data stream;

form a first plurality of feature time series waveforms which respectively correspond to spectrally distinct portions of the received data stream;

store a second plurality of feature time series

waveforms;

correlate the first plurality of feature time series waveforms with the second plurality of feature time series waveforms in an order corresponding to (i) a map of candidate patterns from the second plurality of feature time series waveforms that best match the rank ordering of the first plurality of feature time series waveforms and (ii) the rank ordering of second plurality of feature time series waveforms; and

designate a recognition when a correlation probability value between the first plurality of feature time series waveforms and at least one of the second plurality of feature time series waveforms reaches a predetermined value.

24. (Currently Amended) A computer readable storage medium which stores a program which causes one or more computers to form video features from an input video stream, the program causing the at least one computer to;

receive an input video stream which corresponds to a video screen having a plurality of regions, the video screen comprising a plurality of pixels having intensity and color;

integrate at least one of the intensity and the color of video signals corresponding to each of the plural areas of the video screen;

form a set of low rate time series feature data streams from the integrated video signal;

form overlapping time intervals of the multiple feature streams such that the overlapping time intervals encompass the entire received video frame sequence;

determine the most distinctive information from each time interval;

rank-order the features of the time interval segments according to their distinctness;

transform the rank-ordered time interval segments to produce complex spectra; and

stores the transformed complex spectra as video features.

Al
cont

25. (Currently Amended) A computer readable storage medium which stores a program that causes one or more computers to form audio features from an audio stream, the program causing the one or more computers to:

receive an input audio stream and separating the received audio stream into a plurality of different frequency bands;

extract energy from the plurality of frequency bands;

integrate the energy extracted from each of the plurality of frequency bands;

form multiple feature streams from the integrated energy;

form overlapping time intervals of the multiple feature streams such that the overlapping time intervals encompass the entire received audio stream;

determine the most distinctive information from each time interval;

rank-order the features of the time interval segments according to their distinctness;

transform the rank-ordered time interval segments to produce complex spectra; and

store the transformed complex spectra as audio features.

26. (Currently Amended) A method for forming recognition features from an input data stream, comprising the steps of:

receiving the input data stream;

forming a plurality of feature time series waveforms which respectfully correspond to ~~spectrally~~ distinct portions of the received input data stream;

forming multiple feature streams from the plurality of feature time series waveforms;

forming overlapping time intervals of the multiple feature streams;

estimating the distinctiveness of each feature in each time interval;

rank-ordering the features according to their distinctiveness;

transforming the feature time series to obtain complex spectra; and

storing the feature complex spectra as the recognition features. •

27. (Currently Amended) A method of using recognition features from an input data stream to achieve automatic signal identification, comprising the steps of:

receiving the input data stream;

forming a plurality of time series waveforms which correspond to all features of the received input data stream;

forming multiple feature streams from the plurality of feature time series waveforms;

correlating the most distinctive feature of ~~each~~ plural stored pattern candidate patterns with the ~~corresponding~~ multiple feature streams formed from the unknown input data stream in an order corresponding to a map of candidate patterns that best match the rank ordering of the plurality of feature time series waveforms;

estimating the probability that the resulting correlation value could occur from a random event;


rejecting a candidate pattern if the probability of random detection is above a specified rejection threshold;

accepting a candidate pattern if the probability of random detection is below a specified acceptance threshold;

for unresolved candidate patterns, performing additional correlations with additional features in an order specified by the distinctiveness of each feature;

for unresolved candidate patterns, estimating the combined ~~(joint)~~ probability of random pattern detection;

rejecting a candidate pattern if the combined probability of random detection is above a specified rejection threshold;



accepting a candidate pattern if the combined probability of random detection is below a specified acceptance threshold;


repeating the steps of correlating additional features, updating the combined probability of random detection, and evaluating combined probabilities until a decision can be made for every candidate pattern.

28. (New) An apparatus according to Claim 19, wherein the multiple feature streams are grouped into frames of multiple frequency band energy sampled in time.

29. (New) An apparatus according to Claim 19,

wherein said most distinctive information corresponds to the most reliable features.

30. (New) A method according to claim 20, wherein the map of candidate patterns from the second plurality comprises a set of lists indicating which candidate patterns are most likely to match the first plurality of feature time series waveforms.

 31. (New) A method according to claim 20, wherein recognition is designated when the correlation probability indicates that the error rate is less than a designated threshold.

32. (New) A method according to claim 21, wherein the video stream represents a monochromatic image.

33. (New) The method of claim 21, wherein the video averaging step comprises integrating pixel values from distinct regions of a video frame sequence.

34. (New) The method of claim 21, wherein the low rate video time series streams are formed by time averaging and decimating each of the plural video feature streams.

35. (New) A method according to claim 22, wherein the separation into a plurality of different frequency bands is accomplished through a set of bandpass filters.

36. (New) A method according to claim 22, wherein the separation into a plurality of different frequency bands is accomplished through spectral analysis using at least one of a DFT, FFT, and DCT transform.

37. (New) A method according to claim 22, wherein the multiple feature streams are formed by sampling the energy in each of the plurality of frequency bands.


38. (New) A method according to claim 22, wherein the multiple feature streams form overlapping time intervals that (i) are redundant and (ii) provide no gaps between time interval segments.

39. (New) A method according to claim 22, wherein the multiple feature streams within each time interval are rank ordered according to their reliability.

40. (New) Computer readable storage medium according to claim 23, wherein time series waveforms from the first plurality of feature time series waveforms are matched

with corresponding time series waveforms from the second plurality of feature time series waveforms in an order determined from the relative reliability of the individual features.

41. (New) Computer readable storage medium according to claim 23, wherein recognition is designated when the joint probability of multiple feature correlations indicates that random detection is not probable.

 42. (New) Computer readable storage medium according to claim 24, wherein the multiple feature streams are formed by filtering and sampling the plural integrated regions from a sequence of video frames.

43. (New) Computer readable storage medium according to claim 24, wherein the multiple feature streams form overlapping time intervals that (i) are redundant and (ii) provide no gaps between time interval segments.


44. (New) Computer readable storage medium according to claim 26, wherein the multiple feature streams are formed from an audio signal.

45. (New) Computer readable storage medium

according to claim 26, wherein their multiple feature streams are formed from a video signal.

46. (New) A method according to claim 26, where the input data stream comprises audio.

47. (New) A method according to claim 26, where the input data stream comprises video.

 48. (New) A method according to claim 26, where the input data stream comprises both audio and video.

49. (New) A method according to claim 27, where the candidate patterns stored in the database are correlated with similar features of the multiple feature streams formed from the unknown input according to a reliability of each feature in identifying the unknown input.

50. (New) A method according to claim 27, where the multiple feature streams of the unknown input are ranked ordered according to their distinctiveness and reliability.

51. (New) A method according to claim 27, where the rank ordered multiple feature streams of the unknown input are used to access a lookup table of links to the most

likely patterns stored in the database.

P1
OK
